

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 0502131000
Product name: MOOD ACTIVATOR 5 VOL NEW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses	Industrial	Professional	Consumer
activator for hair dyeing and bleaching products	-	✓	-

Uses Advised Against

Do not use other than as indicated.

1.3. Details of the supplier of the safety data sheet

Name: PIDIELLE S.p.A.
Full address: VIA BERGAMINA, 7
District and Country: 20014 NERVIANO (MI)
Italia
Tel. +39 0331 580 166
Fax +39 0331 485 677

e-mail address of the competent person

responsible for the Safety Data Sheet: sds@elgoncosmetic.it
Product distribution by: PIDIELLE S.p.A.

1.4. Emergency telephone number

For urgent inquiries refer to

+39 0331 580 166

Numeri telefonici dei principali Centri Antiveleni italiani (attivi 24/24 ore)

Centro Antiveleni di Pavia 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia)
Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca' Granda - Milano)
Centro Antiveleni di Bergamo 800 883300 (CAV Ospedali Riuniti - Bergamo)
Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze)
Centro Antiveleni di Roma 06 305434 (CAV Policlinico Gemelli - Roma)
Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma)
Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli)
Centro Antiveleni di Foggia 0881 732326 (Az. Osp. Univ. Foggia)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

MOOD ACTIVATOR 5 VOL NEW

Hazard classification and indication:

Skin corrosion, category 1A

H314

Causes severe skin burns and eye damage.

Serious eye damage, category 1

H318

Causes serious eye damage.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H314

Causes severe skin burns and eye damage.

Precautionary statements:

P260

Do not breathe dust / fume / gas / mist / vapours / spray.

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P303+P361+P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P280

Wear protective gloves/ protective clothing / eye protection / face protection.

P310

Immediately call a POISON CENTER / doctor / . . .

P264

Wash with water thoroughly after handling.

Contains:

HYDROGEN PEROXIDE SOLUTION

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification

x = Conc. %

Classification 1272/2008 (CLP)

HYDROGEN PEROXIDE
SOLUTION

CAS 7722-84-1

 $1,5 \leq x < 2$ Ox. Liq. 1 H271, Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Corr. 1A H314,
Eye Dam. 1 H318, STOT SE 3 H335, Classification note according to Annex
VI to the CLP Regulation: B

EC 231-765-0

INDEX 008-003-00-9

MOOD ACTIVATOR 5 VOL NEW

Reg. no. 01-2119485845-22

LAURYL ALCOHOL

CAS 112-53-8

$0,45 \leq x < 0,5$

Eye Irrit. 2 H319, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411

EC 203-982-0

INDEX -

Reg. no. 01-2119485976-15-XXXX

MYRISTYL ALCOHOL

CAS 112-72-1

$0,15 \leq x < 0,2$

Eye Irrit. 2 H319, Aquatic Chronic 1 H410 M=1

EC 204-000-3

INDEX -

Reg. no. 01-2119485910-33-XXXX

PHOSPHORIC ACID

CAS 7664-38-2

$0,05 \leq x < 0,1$

Skin Corr. 1B H314, Eye Dam. 1 H318, Classification note according to Annex VI to the CLP Regulation: B

EC 231-633-2

INDEX 015-011-00-6

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

MOOD ACTIVATOR 5 VOL NEW

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

MOOD ACTIVATOR 5 VOL NEW

Regulatory References:

ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition,published 2018)
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2019

HYDROGEN PEROXIDE SOLUTION

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	1,4	1			
WEL	GBR	1,4	1	2,8	2	
TLV-ACGIH		1,4	1			

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,01	mg/l
Normal value in marine water	1	mg/l
Normal value for fresh water sediment	0,04	mg/kg
Normal value for marine water sediment	0,04	mg/kg
Normal value of STP microorganisms	4,66	mg/l
Normal value for the terrestrial compartment	0	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Chronic systemic	Effects on workers			Chronic systemic
	Acute local	Acute systemic	Chronic local		Acute local	Acute systemic	Chronic local	
Inhalation	1,93 mg/m3		0,21 mg/m3		3 mg/m3		1,4 mg/m3	

LAURYL ALCOHOL

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,0028	mg/l
Normal value in marine water	0,00028	mg/l
Normal value for fresh water sediment	1,1	mg/kg
Normal value for marine water sediment	0,11	mg/kg
Normal value of STP microorganisms	0,021	mg/l
Normal value for the terrestrial compartment	0,888	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Chronic systemic	Effects on workers			Chronic systemic
	Acute local	Acute systemic	Chronic local		Acute local	Acute systemic	Chronic local	
Oral		75 mg/kg bw/d		75 mg/kg bw/d				
Inhalation		65 mg/m3		65 mg/m3		220 mg/m3		220 mg/m3
Skin		75 mg/kg bw/d		75 mg/kg bw/d		125 mg/kg bw/d		125 mg/kg bw/d

MYRISTYL ALCOHOL

Predicted no-effect concentration - PNEC

MOOD ACTIVATOR 5 VOL NEW

Normal value in fresh water	0,00032	mg/l
Normal value in marine water	0,000032	mg/l
Normal value for fresh water sediment	0,36	mg/kg
Normal value for marine water sediment	0,036	mg/kg
Normal value of STP microorganisms	0,0019	mg/l
Normal value for the terrestrial compartment	0,28	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		75 mg/kg bw/d		75 mg/kg bw/d				
Inhalation		65 mg/m3		65 mg/m3		220 mg/m3		220 mg/m3
Skin		75 mg/kg bw/d		75 mg/kg bw/d		125 mg/kg bw/d		125 mg/kg bw/d

PHOSPHORIC ACID**Threshold Limit Value**

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	ppm	
VLA	ESP	1	2	
WEL	GBR	1	2	
VLEP	ITA	1	2	
OEL	EU	1	2	
TLV-ACGIH		1	3	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

MOOD ACTIVATOR 5 VOL NEW

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	fluid cream	
Colour	white	
Odour	characteristic	
Odour threshold	Not available	
pH	2,0 - 2,5	
Melting point / freezing point	Not available	
Initial boiling point	Not available	
Boiling range	Not available	
Flash point	> 60 °C	
Evaporation rate	Not available	
Flammability (solid, gas)	Not available	
Lower inflammability limit	Not available	
Upper inflammability limit	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Vapour pressure	Not available	
Vapour density	Not available	
Relative density	0,99 - 1,01 g/ml	Temperature:20 °C
Solubility	Not available	
Partition coefficient: n-octanol/water	Not available	
Auto-ignition temperature	Not available	
Decomposition temperature	Not available	
Viscosity	500 - 2000 mPa x sec	Temperature:20 °C
Explosive properties	Not available	
Oxidising properties	Not available	

9.2. Other information

Title of hydrogen peroxide	1,3 - 1,7 %
----------------------------	-------------

SECTION 10. Stability and reactivity**10.1. Reactivity**

HYDROGEN PEROXIDE SOLUTION

Decomposes if exposed to: light,heat.Decomposes on contact with: alkaline metals.Possibility of explosion.

PHOSPHORIC ACID

Decomposes at temperatures above 200°C/392°F.

10.2. Chemical stability

Information not available

10.3. Possibility of hazardous reactions

The product may react violently with water.

PHOSPHORIC ACID

Risk of explosion on contact with: nitromethane.May react dangerously with: alkalis,sodium borohydride.

10.4. Conditions to avoid

Avoid overheating. Prevent moisture or water from penetrating inside the containers.

HYDROGEN PEROXIDE SOLUTION

Avoid exposure to: light,heat.Avoid contact with: alkaline substances.

10.5. Incompatible materials

HYDROGEN PEROXIDE SOLUTION

Incompatible with: flammable substances,acetone,ethanol,glycerol,organic substances,iron,copper,bronze,chromium,zinc,lead,silver,manganese,acetic acid.

sulphides,hydrated

bases,oxidising

PHOSPHORIC ACID

Incompatible with: metals,strong alkalis,aldehydes,organic sulphides,peroxides.

10.6. Hazardous decomposition products

PHOSPHORIC ACID

May develop: phosphoryl oxides.

SECTION 11. Toxicological information

MOOD ACTIVATOR 5 VOL NEW

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effectsMetabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

> 20 mg/l

LD50 (Oral) of the mixture:

>2000 mg/kg

LD50 (Dermal) of the mixture:

Not classified (no significant component)

MYRISTYL ALCOHOL

LD50 (Oral) > 2000 mg/kg rat

LD50 (Dermal) > 2000 mg/kg rabbit

LC50 (Inhalation) > 1,5 mg/l/1h rat

LAURYL ALCOHOL

LD50 (Oral) > 2000 mg/kg rat

LD50 (Dermal) > 2000 mg/kg rabbit

LC50 (Inhalation) > 71 mg/l/1h rat

HYDROGEN PEROXIDE SOLUTION

LD50 (Oral) 693,7 mg/kg Rat

MOOD ACTIVATOR 5 VOL NEW

at the concentration of 35%

PHOSPHORIC ACID

LD50 (Oral) 1530 mg/kg Rat

LD50 (Dermal) 2740 mg/kg Rabbit

LC50 (Inhalation) > 0,85 mg/l/1h Rat

SKIN CORROSION / IRRITATION

Corrosive for the skin

Classification according to the experimental Ph value

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

MOOD ACTIVATOR 5 VOL NEW

12.1. Toxicity

MYRISTYL ALCOHOL

LC50 - for Fish	> 1 mg/l/96h
EC50 - for Crustacea	3,2 mg/l/48h Dafnie
EC50 - for Algae / Aquatic Plants	> 10 mg/l/72h
Chronic NOEC for Crustacea	> 0,001 mg/l Daphnia magna

LAURYL ALCOHOL

LC50 - for Fish	> 1 mg/l/96h Phimepales promelas
EC50 - for Crustacea	> 0,1 mg/l/48h Daphnia magna
Chronic NOEC for Algae / Aquatic Plants	0,085 mg/l Desmodesmus subspicatus

HYDROGEN PEROXIDE SOLUTION

LC50 - for Fish	16,4 mg/l/96h Pimepales promelas
EC50 - for Crustacea	2,4 mg/l/48h Daphnia
EC50 - for Algae / Aquatic Plants	1,38 mg/l/72h Skeletonema costatum

12.2. Persistence and degradability

MYRISTYL ALCOHOL

Rapidly degradable

HYDROGENATED COCONUT OIL

Rapidly degradable

LAURYL ALCOHOL

Rapidly degradable

HYDROGEN PEROXIDE SOLUTION

Solubility in water 100000 mg/l

Rapidly degradable

PHOSPHORIC ACID

Solubility in water > 850000 mg/l

Degradability: information not available

12.3. Bioaccumulative potential

HYDROGEN PEROXIDE SOLUTION

Partition coefficient: n-octanol/water -1,57

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

MOOD ACTIVATOR 5 VOL NEW

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006Product

Point 3

Contained substancePoint 75 OXYQUINOLINE
SULFATESubstances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

MOOD ACTIVATOR 5 VOL NEW

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

LAURYL ALCOHOL

MYRISTYL ALCOHOL

SECTION 16. Other information

Finished cosmetic products are excluded from EC Regulation 1907/2006 (REACH) as regards the safety data sheet requirements (art. 31 and 32) (2). Finished cosmetic products are completely excluded from the field of application of Regulation 1272/2008 (CLP) (3), as previously established by Directive 1999/45/EC on dangerous preparations (4), and as such are exempt from danger classification and labelling obligations and the provisions relating to safety data sheets [art. 1 (3) (c) of Regulation 1272/2008 and Directive 1999/45].

This Sheet is not to be regarded as a Safety Data Sheet but purely as a hygiene and safety information tool drafted to help employers fulfil the obligations of Leg. Decree 81/08. In fact, professional users are protected by Leg. Decree 81/08 as amended, which obliges employers to carry out a risk assessment for the health and safety of their workers (art. 28 Leg. Decree 81/08). This decree defines (heading IX, art. 222) as dangerous chemical agents not only the substances and mixtures that correspond to the classification criteria of the relevant laws, but also agents that may pose a risk to the health and safety of workers because of their chemical-physical, chemical or toxicological properties and the way in which they are used or present in the workplace, including chemical agents that have been assigned an occupational exposure limit value (art. 222 (1)(b)(3)). More specifically, Regulation 122/2009 defines the end user as a consumer or professional that uses the cosmetic product (1), making no distinction between these two figures.

1 (EC) Regulation no. 1223/2009 of the European Parliament and of the Council of 30 November 2009 on cosmetic products, article 2, paragraph 1, letter f.

2 (EC) Regulation no. 1907/2006 of the European Parliament and of the Council of 18 December 2006, concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH).

3 (EC) Regulation no. 1272/2008 of the European Parliament and of the Council of 16 December 2008 regarding the classification, labelling and packaging of substances and mixtures

4 Directive 1999/45/EC of the European Parliament and of the Council of 31 May 1999 concerning the approximation of the laws, regulations and administrative provisions of the Member States relating to the classification, packaging and labelling of dangerous preparations.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Ox. Liq. 1	Oxidising liquid, category 1
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H271	May cause fire or explosion; strong oxidiser.
H302	Harmful if swallowed.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.

MOOD ACTIVATOR 5 VOL NEW

H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website

MOOD ACTIVATOR 5 VOL NEW

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.