

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 1102030150
Product name: MOOD STYLING GLUE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses	Industrial	Professional	Consumer
hair styling cream	-	✓	-

Uses Advised Against

Do not use other than as indicated.

1.3. Details of the supplier of the safety data sheet

Name: PIDIELLE S.p.A.
Full address: VIA BERGAMINA, 7
District and Country: 20014 NERVIANO (MI)
Italia
Tel. +39 0331 580 166
Fax +39 0331 485 677

e-mail address of the competent person

responsible for the Safety Data Sheet: sds@elgoncosmetic.it
Product distribution by: PIDIELLE S.p.A.

1.4. Emergency telephone number

For urgent inquiries refer to

+39 0331 580 166**Numeri telefonici dei principali Centri Antiveleni italiani (attivi 24/24 ore)**

Centro Antiveleni di Pavia 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia)
Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca' Granda - Milano)
Centro Antiveleni di Bergamo 800 883300 (CAV Ospedali Riuniti - Bergamo)
Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze)
Centro Antiveleni di Roma 06 305434 (CAV Policlinico Gemelli - Roma)
Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma)
Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli)
Centro Antiveleni di Foggia 0881 732326 (Az. Osp. Univ. Foggia)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

MOOD STYLING GLUE

Hazard classification and indication:

Flammable liquid, category 2
Aspiration hazard, category 1

H225
H304

Highly flammable liquid and vapour.
May be fatal if swallowed and enters airways.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331 Do NOT induce vomiting.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER / doctor / . . .
P370+P378 In case of fire: use CO2, powder for fire extinguisher, water spray or foaming liquids to extinguish.
P233 Keep container tightly closed.

Contains: PARAFFINUM LIQUIDUM

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
PARAFFINUM LIQUIDUM		
CAS 8042-47-5	$10 \leq x < 11,5$	Asp. Tox. 1 H304
EC 232-455-8		
INDEX -		
Reg. no. 01-2119487078-27-0000		

MOOD STYLING GLUE

ETHANOLCAS 64-17-5 $9 \leq x < 10,5$ Flam. Liq. 2 H225

EC 200-578-6

INDEX 603-002-00-5

Reg. no. 01-2119457610-43-XXXX

BHTCAS 128-37-0 $0 \leq x < 0,05$ Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 204-881-4

INDEX -

Reg. no. 01-2119480433-40

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

MOOD STYLING GLUE

8.1. Control parameters

Regulatory References:

ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition,published 2018)
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2019

PARAFFINUM LIQUIDUM

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				40 mg/kg bw/d				
Inhalation				35 mg/m3				160 mg/m3
Skin				92 mg/kg bw/d				220 mg/kg bw/d

ETHANOL

Threshold Limit Value

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	ppm	mg/m3 ppm
VLA	ESP		1910	1000
WEL	GBR	1920	1000	
TLV-ACGIH			1884	1000

BHT

Threshold Limit Value

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	ppm	mg/m3 ppm
OEL	EU	2		

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					2 mg/m3			

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	cream gel	
Colour	white	
Odour	characteristic	
Odour threshold	Not available	
pH	6,5 - 7,5	
Melting point / freezing point	Not available	
Initial boiling point	> 35 °C	
Boiling range	Not available	
Flash point	< 23 °C	
Evaporation rate	Not available	
Flammability (solid, gas)	Not available	
Lower inflammability limit	Not available	
Upper inflammability limit	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Vapour pressure	Not available	
Vapour density	Not available	
Relative density	1,00 - 1,02 g/ml	Temperature: 20 °C
Solubility	Not available	

MOOD STYLING GLUE

Partition coefficient: n-octanol/water	Not available	
Auto-ignition temperature	Not available	
Decomposition temperature	Not available	
Viscosity	50000 - 100000 mPa x sec	Temperature:20 °C
Explosive properties	Not available	
Oxidising properties	Not available	

9.2. Other information

Information not available

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

BHT

Avoid exposure to: heat,light,moist air.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

ETHANOL

Risk of explosion on contact with: alkaline metals,alkaline oxides,calcium hypochlorite,sulphur monofluoride,acetic anhydride,acids,concentrated hydrogen peroxide,perchlorates,perchloric acid,perchloronitrile,mercury nitrate,nitric acid,silver,silver nitrate,ammonia,silver oxide,ammonia,strong oxidising agents,nitrogen dioxide.May react dangerously with: bromoacetylene,chlorine acetylene,bromine trifluoride,chromium trioxide,chromyl chloride,fluorine,potassium tert-butoxide,lithium hydride,phosphorus trioxide,black platinum,zirconium (IV) chloride,zirconium (IV) iodide.Forms explosive mixtures with: air.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

ETHANOL

Avoid exposure to: sources of heat,naked flames.

10.5. Incompatible materials

BHT

Incompatible with: oxygen,oxidising substances.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

VP/VA COPOLYMER

LD50 (Oral) > 630 mg/kg RAT

PARAFFINUM LIQUIDUM

LD50 (Oral) > 5000 mg/m3 rat

LD50 (Dermal) > 2000 mg/m3 rabbit

LC50 (Inhalation) > 5000 mg/m3 rat

GLYCERIN

MOOD STYLING GLUE

LD50 (Oral) 10 mg/kg guinea pigs

STEARYL ALCOHOL

LD50 (Oral) > 2000 mg/kg rat

LD50 (Dermal) > 5000 mg/kg rabbit

CETYL ALCOHOL

LD50 (Oral) > 2000 mg/kg rat

LD50 (Dermal) > 5000 mg/kg

LC50 (Inhalation) > 1,5 mg//1h

BHT

LD50 (Oral) > 890 mg/kg rat

LD50 (Dermal) > 2000 mg/kg rabbit

ETHANOL

LD50 (Oral) > 5000 mg/kg Rat

LC50 (Inhalation) 120 mg//4h Pimephales promelas

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

PARAFFINUM LIQUIDUM

EC50 - for Crustacea 100 mg/l/48h

EC50 - for Algae / Aquatic Plants 100 mg/l/72h

GLYCERIN

LC50 - for Fish > 1000 mg/l/96h

BHT

LC50 - for Fish > 0,57 mg/l/96h

EC50 - for Crustacea > 0,31 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants 0,72 mg/l/72h

12.2. Persistence and degradability

STEARYL ALCOHOL

Rapidly degradable

CETYL ALCOHOL

Rapidly degradable

ETHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

12.3. Bioaccumulative potential

MOOD STYLING GLUE

PARAFFINUM LIQUIDUM

Partition coefficient: n-octanol/water > 3,5 Kow

BHT

Partition coefficient: n-octanol/water 5

BCF 646 mg/l

ETHANOL

Partition coefficient: n-octanol/water -0,35

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number**

ADR / RID, IMDG, 1170
IATA:

14.2. UN proper shipping name

ADR / RID: ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

IMDG: ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

IATA: ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es)

MOOD STYLING GLUE

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3

**14.4. Packing group**ADR / RID, IMDG, II
IATA:**14.5. Environmental hazards**

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 33

Limited
Quantities: 1
LTunnel
restriction
code: (D/E)IMDG: Special Provision: -
EMS: F-E, S-DLimited
Quantities: 1
L

IATA: Cargo:

Maximum
quantity: 60 L

Pass.:

Maximum
quantity: 5 L

Special Instructions:

A3, A58,
A180Packaging
instructions:
364
Packaging
instructions:
353**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

MOOD STYLING GLUE

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Finished cosmetic products are excluded from EC Regulation 1907/2006 (REACH) as regards the safety data sheet requirements (art. 31 and 32) (2). Finished cosmetic products are completely excluded from the field of application of Regulation 1272/2008 (CLP) (3), as previously established by Directive 1999/45/EC on dangerous preparations (4), and as such are exempt from danger classification and labelling obligations and the provisions relating to safety data sheets [art. 1 (3) (c) of Regulation 1272/2008 and Directive 1999/45].

This Sheet is not to be regarded as a Safety Data Sheet but purely as a hygiene and safety information tool drafted to help employers fulfil the obligations of Leg. Decree 81/08. In fact, professional users are protected by Leg. Decree 81/08 as amended, which obliges employers to carry out a risk assessment for the health and safety of their workers (art. 28 Leg. Decree 81/08). This decree defines (heading IX, art. 222) as dangerous chemical agents not only the substances and mixtures that correspond to the classification criteria of the relevant laws, but also agents that may pose a risk to the health and safety of workers because of their chemical-physical, chemical or toxicological properties and the way in which they are used or present in the workplace, including chemical agents that have been assigned an occupational exposure limit value (art. 222 (1)(b)(3)). More specifically, Regulation 1222/2009 defines the end user as a consumer or professional that uses the cosmetic product (1), making no distinction between these two figures.

1 (EC) Regulation no. 1223/2009 of the European Parliament and of the Council of 30 November 2009 on cosmetic products, article 2, paragraph 1, letter f.

2 (EC) Regulation no. 1907/2006 of the European Parliament and of the Council of 18 December 2006, concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH).

3 (EC) Regulation no. 1272/2008 of the European Parliament and of the Council of 16 December 2008 regarding the classification, labelling and packaging of substances and mixtures

4 Directive 1999/45/EC of the European Parliament and of the Council of 31 May 1999 concerning the approximation of the laws, regulations and administrative provisions of the Member States relating to the classification, packaging and labelling of dangerous preparations.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2

Asp. Tox. 1 Aspiration hazard, category 1

MOOD STYLING GLUE

Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website

MOOD STYLING GLUE

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.